

SPECIFICATIONS - 100 Degree Rise

PHYSICAL

MODEL	TANK/ GALLONS	LENGTH	WIDTH	HEIGHT	WEIGHT/ LBS.
P-3-2W	3,000	23' 5"	6' 0"	6' 6"	9,000
P-5-3W	5,000	22' 5"	7' 8"	8' 2"	10,000
P-5-6W	5,000	22' 5"	7' 8"	8' 2"	11,000
P-5-10W	5,000	22' 5"	7' 8"	8' 2"	11,000
P-8-6W	8,000	26' 5"	8' 7"	9' 3"	12,000
P-10-6W	10,000	32' 2"	8' 7"	9' 3"	18,000
P-10-10W	10,000	32' 2"	8' 7"	9' 3"	18,000
P-10-15W	10,000	32' 2"	8' 7"	9' 3"	18,000
P-10-20W	10,000	32' 2"	8' 7"	9' 3"	18,000
P-15-10W	15,000	28' 7"	11' 1"	12' 0"	20,000
P-15-15W	15,000	28' 7"	11' 1"	12' 0"	20,000
P-15-20W	15,000	28' 7"	11' 1"	12' 0"	20,000
P-20-10W	20,000	36' 5"	11' 1"	12' 0"	26,000
P-20-15W	20,000	36' 5"	11' 1"	12' 0"	26,000
P-20-20W	20,000	36' 5"	11' 1"	12' 0"	26,000
P-25-15W	25,000	44' 2"	11' 1"	12' 0"	31,000
P-25-20W	25,000	44' 2"	11' 1"	12' 0"	31,000
P-30-20W	30,000	51' 2"	11' 1"	12' 0"	38,000
P-15-2-20W	15,000	28' 7"	11' 1"	12' 0"	27,000
P-20-2-20W	20,000	36' 5"	11' 1"	12' 0"	33,000
P-25-2-20W	25,000	44' 2"	11' 1"	12' 0"	35,000
P-30-2-20W	30,000	51' 2"	11' 1"	12' 0"	45,000

OPERATING CAPACITIES

MODEL	MIN MAKE UP WATER GPM/FLOW RATE	HOURLY RECOVERY RATE GAL/100 RISE	AVAILABLE GAL 1ST HR, 100 RISE	TOTAL USABLE GAL 8 HR/ 100 RISE
P-3-2W	4.7	283	3,282	5,256
P-5-3W	7.0	423	5,423	8,384
P-5-6W	14.1	846	5,846	11,768
P-5-10W	23.5	1,410	6,410	16,280
P-8-6W	14.1	846	8,846	14,768
P-10-6W	14.1	846	10,846	16,768
P-10-10W	23.5	1,410	11,410	21,280
P-10-15W	35.5	2,115	12,115	26,920
P-10-20W	47.0	2,820	12,820	32,560
P-15-10W	23.5	1,410	16,410	26,280
P-15-15W	35.5	2,115	17,115	31,920
P-15-20W	47.0	2,820	17,820	37,560
P-20-10W	23.5	1,410	21,410	31,280
P-20-15W	35.5	2,115	22,115	36,920
P-20-20W	47.0	2,820	22,820	42,560
P-25-15W	35.5	2,115	27,115	41,920
P-25-20W	47.0	2,820	27,820	47,560
P-30-20W	47.0	2,820	32,820	52,560
P-15-2-20W	94	5,640	20,640	60,120
P-20-2-20W	94	5,640	25,640	65,120
P-25-2-20W	94.0	5,640	30,640	70,120
P-30-2-20W	94.0	5,640	35,640	75,120